

DATA SHEET

PLASTER PRIMER



SOLVENT-BASED & ALKALI RESISTANT. SUITABLE FOR CEMENT PLASTER, CONCRETE, BRICK, GYPSUM PLASTER, FIBRE CEMENT

SECTION A: DESCRIPTION

A solvent-base pigmented primer recommended for both interior and exterior plaster. With alkali-resistance for use on sound cement, concrete and brick substrates. Provides adhesion for subsequent top-coats and provides good opacity over most surfaces. Do not apply to damp surfaces (e.g. newly rendered plaster or cement). This product must be used in conjunction with either Excelsior Bonding Liquid or Excelsior Surfcon if the surface is very powdery or friable. Not suitable for Rhinolite or Gypsum plaster.

SECTION B: COMPOSITION

Modified Alkali resin in Hydrocarbon solvent.

SECTION C: PHYSICAL PROPERTIES

Colour:	White
Appearance:	Dries to a matt finish
Viscosity:	75 - 85 Ku @ 25°C.
S.G.:	1.20 - 1.25
Mass Solids:	47 - 52%
Volume Solids	28 - 33%
Shelf Life:	12 months
Storage Conditions:	Away from direct sunlight, heat and/or naked flame
Pack Size:	1l, 5l, 20l, 200l
Drying time:	Touch-dry 4 hours, hard dry 18 hours @ 25°C.
Recoating time:	18 Hours
Spread Ratio:	4 - 8m ² /l

SECTION D: APPLICATION PROPERTIES

Product is supplied ready-for-use, but can be thinned with turpentine $\pm 10\%$ for better penetration. Apply by a brush or roller also by spray.

SECTION E: CLEANING

Wash implements with turpentine while still wet.

SECTION F: PRECAUTION

Flash point:	43°C (contains flammable solvent)
Toxicity:	See M.S.D.S. (contains flammable solvent)

SECTION G IMPORTANT!

- Stir well before use.
- Allow 7 days to cure before washing.
- Do not paint if rain is imminent or in damp conditions.

SAFETY INFORMATION

- Ensure adequate ventilation when painting and wear the appropriate safety equipment (i.e. gloves, eye protection, and dust mask for spraying)
- Keep out of reach of children
- If accidental contact with skin, wash immediately with soap and water
- Eye contact, in the event of eye contact rinse well with copious amounts of water and contact a doctor immediately
- Ingestion: if the product is swallowed seek immediate medical attention and do not induce vomiting
- Flammable: do not smoke while painting, store in a cool dry place away from naked flame, gas, heat and any possible ignition sources (i.e. welding or grinding sparks)
- Should you have any queries or require more information, please contact Mylaw Technical Services +27 11 474 1900



DATA SHEET

PLASTER PRIMER

SOLVENT-BASED & ALKALI RESISTANT. SUITABLE FOR CEMENT PLASTER,
CONCRETE, BRICK, GYPSUM PLASTER, FIBRE CEMENT



SECTION G: NOTE

No guarantees are implied by the recommendations contained herein; since the data sheet is issued for information only. Method of application, surface cleanliness, conditions of use etc. are beyond our control.

