


DATA SHEET



TRADE ACRYLIC

- EXCELLENT WHITENESS • HIGH OBLITERATION

SECTION A: DESCRIPTION

An economical general purpose matt acrylic paint for interior and exterior surfaces (recommended interior) available in a white and a range of colour card colours. With limited washability.

SECTION B: COMPOSITION

Co-polymer emulsion

SECTION C: PHYSICAL PROPERTIES

Colour:	White and as per colour card
Appearance:	Matt
Gloss:	<15% @ 85°
Viscosity:	90 - 105 Ku @ 25°C
S.G.:	1.25 - 1.30
Mass Solids:	34 - 39%
Volume Solids:	17 - 22%
Shelf Life:	12 Months
Storage Conditions:	Normal
Pack Size:	5l, 20l

SECTION D: APPLICATION PROPERTIES

Method:	Brush, airless spray or roller
Spreading Rate:	4 - 8m ² /l
Number of coats:	2
Drying Time @ 25°C:	Hard 4hrs (depending on moisture and humidity). Allow 14 days to cure before washing.
Overcoating Time @ 25°C:	4hrs
Thinning:	Not Applicable
Cleaning Solvent:	Water
Recommended systems:	As described above

SECTION E: PRECAUTION

Flash point:	Water-based
Toxicity:	see M.S.D.S.

SECTION F: SURFACE PREPARATION

- All surfaces to be thoroughly clean, dry and free from grease, dirt or flaking paint.
- All loosely adhering material and powder such as distemper or lime must be removed, one coat of Excelsior BONDING LIQUID applied and allowed to dry (18 hours).

Metal surfaces must be primed with the appropriate primer.

GALVANISED IRON

Remove storage oil with Excelsior GI CLEANER and prime with one coat of AQUA METALPRIME.

MILD STEEL TO BE PRIMED WITH:

- Excelsior AQUA METALPRIME water-based primer.
- Alkyd based ExcelsiorGP RED OXIDE PRIMER or ZP PRIMER (with anti-corrosive zinc-phosphate pigments).

FRESH PLASTER:

Once plaster is completely dry. Apply one coat of:

- Qolor PLASTER PRIMER (water-based).



DATA SHEET

TRADE ACRYLIC

- EXCELLENT WHITENESS
- HIGH OBLITERATION



PREVIOUSLY PAINTED EMULSION (PVA/ACRYLIC SURFACES)

- Loose material must be removed with sandpaper.
- Powdery surfaces sealed with Excelsior BONDING LIQUID.
- Dirt or grime to be removed with sugar soap.

PREVIOUSLY PAINTED ENAMEL (Hi-gloss or Eggshell) SURFACES

- Sandpaper thoroughly.
- Apply one coat of Qolor UNIVERSAL UNDERCOAT and allow to dry 18 hours.

IMPORTANT!

- Stir well before use.
- Allow 7 days to cure before washing.
- Do not paint if rain is imminent or in damp conditions.

SAFETY INFORMATION

- Keep out of reach of children.
- Ensure adequate ventilation during use.
- Do not smoke or eat while painting.
- Avoid contact with eyes and skin: rinse with water and consult a doctor.
- If ingested seek medical attention immediately and do not induce vomiting.
- Store container in a cool and dry area.

SECTION G: NOTE

No guarantees are implied by the recommendations contained herein; since the data sheet is issued for information only. Method of application, surface cleanliness, conditions of use etc. are beyond our control.

