

# DATA SHEET

## WALL SATIN ACRYLIC



8  
YEAR+  
LIFE EXPECTANCY

Qolor  
switched on Coatings!

- FULLY WASHABLE AND WATER RESISTANT
- DIRT RESISTANT • UV RESISTANT

### SECTION A: DESCRIPTION

A good quality general purpose non yellowing waterbased sheen acrylic paint for interior and exterior surfaces. Excellent opacity and stain resistance with good scrubability available in a white and a range of colour card colours. Formulated to meet requirements of SABS 1586 GRADE 2.

### SECTION B: COMPOSITION

Co-polymer emulsion based.

### SECTION C: PHYSICAL PROPERTIES

Colour:	White and as per colour card
Appearance:	Sheen
Gloss:	35 - 45% @ 85°
Viscosity:	95 - 100 Ku @ 25°C
S.G.:	1.20 - 1.25
Mass Solids:	38 - 43%
Volume solids:	24 - 29%
Shelf Life:	12 Months
Storage Conditions:	Normal
Pack Size:	1l, 5l, 20l

### SECTION D: APPLICATION PROPERTIES

Method:	Brush, airless spray or roller
Recommended WFT:	100um per coat
Spreading Rate:	8 - 10m <sup>2</sup> /l
Number of coats:	Two
Drying Time @ 25°C:	Hard 4hrs (depending on moisture and humidity). Allow 14 days to cure before washing.
Overcoating Time @ 25°C:	4hrs
Cleaning Solvent:	Water
Recommended systems:	As described above

### SECTION E: PRECAUTION

Flash point:	Water-based
Toxicity:	See M.S.D.S.

### SECTION F: SURFACE PREPARATION

- All surfaces must be thoroughly clean, dry, free from grease, dirt or old flaking paint.
- All loosely adhering material and powder, i.e. Distemper or Lime, must be removed and a coat of Excelsior BONDING LIQUID or SURFCON be applied and allow ±18 hours to dry.

#### NEW WOODWORK

- Rub down with fine sandpaper and seal knots.
- Prime with Excelsior WOOD PRIMER.
- Follow with one coat Qolor UNIVERSAL UNDERCOAT.

#### NEW METAL SURFACES

- Metal surfaces must be primed with the appropriate primer!

#### A. NEW GALVANISED IRON

- Remove storage oil with Excelsior GALVANISED IRON CLEANER and prime with one coat of
- Excelsior AQUA-METALPRIME anti-corrosive primer.



# DATA SHEET

# WALL SATIN ACRYLIC

8  
YEAR+  
LIFE EXPECTANCY

Qolor  
switched on Coatings!

- FULLY WASHABLE AND WATER RESISTANT
- DIRT RESISTANT • UV RESISTANT

## B. NEW MILD STEEL

- Prime with H2O PRIMER RED OXIDE etching water-based primer. (New formulation).  
or Alkyd based GP RED OXIDE PRIMER  
or Excelsior ZP PRIMER (with anti-corrosive Zincphosphate pigments).

## NEW PLASTER

Once plaster is completely dry. Apply one coat of:

- Qolor PLASTER PRIMER.

## PREVIOUSLY PAINTED EMULSION (PVA/Acrylic) SURFACES

- Remove dirt and grime with SUGAR SOAP.
- Loose material must be removed with sandpaper.
- Seal powdery surfaces with Excelsior BONDING LIQUID or SURFCON.

## PREVIOUSLY PAINTED ENAMEL (Hi-gloss or Eggshell) SURFACES

- Sandpaper thoroughly.
- Apply one coat of Qolor UNIVERSAL UNDERCOAT and allow  $\pm 18$  hours to dry.

## IMPORTANT!

- Stir well before use.
- Allow 7 days to cure before washing.
- Do not paint if rain is imminent or in damp conditions.

## SAFETY INFORMATION

- Keep out of reach of children.
- Ensure adequate ventilation during use.
- Do not smoke or eat while painting.
- Avoid contact with eyes and skin: rinse with water and consult a doctor.
- If ingested seek medical attention immediately and do not induce vomiting.
- Store container in a cool and dry area.

## SECTION G: NOTE

No guarantees are implied by the recommendations contained herein; since the data sheet is issued for information only. Method of application, surface cleanliness, conditions of use etc. are beyond our control.

